EARTHGUARD

## **Fiber Matrix**™

Latest independent performance study

NTPEP ASTM 6459 Soil Loss Testing — Impartial 3rd party testing shows EarthGuard outperforms:

- Curlex<sup>®</sup>
- Single and Double Net Straw<sup>™</sup> Blankets
- Single and Double Net Coconut<sup>™</sup> Blankets
- Double Net Straw / Coconut<sup>™</sup> Blankets
- ProMatrix<sup>™</sup>
- Flexterra®
- And Other Commonly Used Hydraulic or Rolled Erosion Control Products

# **Top Performance** & Cost Savings

### Why not go with the best?

Use EarthGuard<sup>®</sup> Fiber Matrix<sup>™</sup> and get the highest returns on your investment. This hydraulically applied, patented technology offers highly rated erosion control along with excellent turbidity reduction and promotes quick growth establishment — all with fast, easy applications and a great price.



# Formulated for your success — EarthGuard.



- Lower your material costs.
- Lower your labor costs.
- Boost your results.

LSC Environmental Products, LLC www.LSCenv.com • sales@LSCenv.com • 800-800-7671





*Two ways to apply. Same great performance.* 



#### EarthGuard Fiber Matrix Bale

EarthGuard soil stabilizer and 100% wood fiber mulch combined in one easy to use 50 lb. bale.



#### EarthGuard Liquid 5 Gallon Container

EarthGuard soil stabilizing concentrate – ready to mix on site with the mulch of your choice.



### Highly Effective. Cost Efficient.

### **Application Rates:**

	<b>Normal Conditions:</b> Maximum Rainfall of < 20" (480 mm) before adequate vegetative establishment											
EARTHGUARD	≤ 4 to 1 Slope		3 to 1 Slope		2 to 1 Slope		≥ 1 to 1 Slope					
CANTINGUAND	Per Acre	Per Ha	Per Acre	Per Ha	Per Acre	Per Ha	Per Acre	Per Ha				
EarthGuard Fiber Matrix	1500 LB	1680 кс	1800 LB	2020 KG	2000 LB	2245 кс	3000 LB	3355 кд				
OR												
EarthGuard Liquid	4-6 GALS	<b>37 - 56</b> LITERS	7 GALS	66 LITERS	8 GALS	75 LITERS	10 GALS	94 LITERS				
Mulch	1500 LB	1680 кс	1800 LB	<b>2020</b> КG	2000 LB	2245 кG	3000 LB	3355 кд				

	<b>Severe Conditions:</b> Maximum Rainfall of > 20" (480 mm) before adequate vegetative establishment											
EARTHGUARD	≤ 5 to ′	1 Slope	4 to 1	Slope	≥ 3 to 1 Slope							
	Per Acre	Per Ha	Per Acre	Per Ha	Per Acre	Per Ha						
EarthGuard Fiber Matrix	2000 LB	2245 КG	2500 LB	2800 КG	3000 LB	3355 кд						
OR												
EarthGuard Liquid	6 GALS	56 LITERS	8 GALS	75 LITERS	10 GALS	94 LITERS						
Mulch	2000 LB	2245 кс	2500 LB	2800 KG	3000 LB	3355 кд						

EarthGuard Liquid can be used for dust control at 10 gallons per acre.



For technical services or to locate your nearest EarthGuard dealer:



Call: 1-800-800-7671 • Email: Sales@LSCenv.com Visit LSC online at: www.LSCenv.com LSC Environmental Products, LLC

2183 Pennsylvania Ave., Apalachin, NY 13732

Information and statements herein are believed to be reliable but are not to be constructed as a warranty or guarantee. Some extreme situations may require higher application rates. LSC Environmental Products, LLC offers no warranties, express or implied. Nothing herein is to be taken as permission to practice any patented invention without a license. EarthGuard<sup>®</sup> is a registered trademark of LSC Environmental Products, LLC. All rights reserved. © 2023 LSC Environmental Products, LLC

#### Solutions for the Greener Good